

UNCLASSIFIED

AD NUMBER

ADB001639

LIMITATION CHANGES

TO:

Approved for public release; distribution is unlimited.

FROM:

Distribution authorized to U.S. Gov't. agencies only; Administrative/Operational Use; 13 FEB 1975. Other requests shall be referred to Department of Defense, Public Affairs Office, Washington, DC 20301.

AUTHORITY

General Elec. ltr, 20 Jun 1975

THIS PAGE IS UNCLASSIFIED

THIS REPORT HAS BEEN DELIMITED
AND CLEARED FOR PUBLIC RELEASE
UNDER DOD DIRECTIVE 5200.20 AND
NO RESTRICTIONS ARE IMPOSED UPON
ITS USE AND DISCLOSURE,

DISTRIBUTION STATEMENT A

APPROVED FOR PUBLIC RELEASE,
DISTRIBUTION UNLIMITED,

BEST COPY
AVAILABLE

AD B001639

TIS Distribution Center
CSP 4-24, X7712
Syracuse, New York 13201

GENERAL ELECTRIC

HEAVY MILITARY EQUIPMENT DEPARTMENT

TECHNICAL INFORMATION SERIES

Author M. M. Fitelson	Subject Category Propagation	No. R74EMH12 Date April 1974
Title THE MEAN OF THE FIELD FOR CYLINDRICALLY SPREADING WAVES IN A RANDOM MEDIUM <i>G.E.</i>		
HMED TIS Distribution Center Box 1122 (CSP 4-24) Syracuse, New York 13201	GE Class 1	No. of Pages
	Govt Class Unclassified	16
<p>Summary</p> <p>The mean value of the field for cylindrically spreading waves in a random medium is obtained when forward scattering is dominant. In addition, the region of validity of the solution is obtained.</p> <p>These results are identical to the corresponding results for plane waves, except for cylindrical spreading loss.</p>		
<p style="text-align: center;">D D C RECEIVED FEB 13 1975 RECEIVED D</p>		

Distribution limited to U.S. Gov't. agencies only. Proprietary Info.: 13 FEB 1975. Other requests for this document must be referred to

This document contains proprietary information of the General Electric Company and is restricted to distribution and use within the General Electric Company unless designated above as GE Class 1 or unless otherwise expressly authorized in writing.

Send to _____

GENERAL ELECTRIC COMPANY TECHNICAL INFORMATION

Within the limitations imposed by Government data export regulations and security classifications, the availability of General Electric Company technical information is regulated by the following classifications in order to safeguard proprietary information:

CLASS 1: GENERAL INFORMATION

Available to anyone on request.
Patent, legal and commercial review
required before issue.

CLASS 2: GENERAL COMPANY INFORMATION

Available to any General Electric Company
employee on request.
Available to any General Electric Subsidiary
or Licensee subject to existing agreements.
Disclosure outside General Electric Company
requires approval of originating component.

CLASS 3: LIMITED AVAILABILITY INFORMATION

Original Distribution to those individuals with
specific need for information.
Subsequent Company availability requires
originating component approval.
Disclosure outside General Electric Company
requires approval of originating component.

CLASS 4: HIGHLY RESTRICTED DISTRIBUTION

Original distribution to those individuals personally responsible for the Company's interests in the subject.
Copies serially numbered, assigned and recorded by name.
Material content, and knowledge of existence, restricted to copy holder.

GOVERNMENT SECURITY CLASSIFICATIONS, when required, take precedence in the handling of the material. Wherever not specifically disallowed, the General Electric classifications should also be included in order to obtain proper handling routines.

GENERAL ELECTRIC COMPANY
HEAVY MILITARY ELECTRONIC SYSTEMS
TECHNICAL INFORMATION SERIES

SECTION Advance Development Engineering
UNIT Advance Sonar Development
HMES ACCOUNTING REFERENCE 572
COLLABORATORS _____
APPROVED S. Garber TITLE Mgr., ASD LOCATION CSP 4-39A, Syracuse, N. Y.

TIS R74EMH12

MINIMUM DISTRIBUTION - Government Unclassified Material (and Title Pages) in G.E. Classes 1, 2, or 3 will be the following.

<u>Copies</u>	<u>Title Page Only</u>	<u>To</u>
0	1	Legal Section, HMES (Syracuse)
0	1	Manager, Technological Planning, HMES (Syracuse)
5	6	G - E Technical Data Center (Schenectady)

MINIMUM DISTRIBUTION - Government Classified Material, Secret or Confidential in G.E. Classes 1, 2, or 3 will be the following.

1	1	Classified Section, Electronics Park Library
1	0	Manager, Technological Planning, HMES (Syracuse)

ADDITIONAL DISTRIBUTION (Keep at minimum within intent of assigned G.E. Class.)

5 (Class 1 Only)

Defense Documentation Center, Cameron Station,
Alexandria, Va. 22314




TABLE OF CONTENTS

<u>Section</u>	<u>Title</u>	<u>Page</u>
I	INTRODUCTION	1-1
II	THE MEAN OF THE FIELD	2-1
III	THE REGION OF VALIDITY OF THE FORWARD SCATTERING EQUATION	3-1
IV	REFERENCES	4-1

SECTION I

INTRODUCTION

In a previous paper (Ref. 1) the author derived the coherence function for the circumstances of the title. In this paper, the mean value of the field is obtained when forward scattering dominates. The region of validity of the solution is obtained.

It is shown that, except for cylindrical spreading loss, the mean value of the field is the same as that of the corresponding plane wave case treated by Tatarskii (Ref. 2). The region of validity is shown to be the same as that of the plane wave case.

As in Reference 1 long range propagation is assumed.

SECTION II

THE MEAN OF THE FIELD

Following Reference 1, let the source be monochromatic and cylindrical with radius ϵ such that

$$k\epsilon \gg 1 \quad (2-1)$$

Let the source radiate into a statistically isotropic and homogeneous medium.

The wave equation in cylindrical coordinates is given by

$$\begin{aligned} \frac{\partial^2 \psi(\rho, s, t)}{\partial \rho^2} + \frac{1}{\rho} \frac{\partial \psi(\rho, s, t)}{\partial \rho} + \Delta(\rho) \psi(\rho, s, t) \\ = \frac{(1 + \mu(\rho, s))^2}{c^2} \frac{\partial^2 \psi(\rho, s, t)}{\partial t^2}; \quad \rho \geq \epsilon \end{aligned} \quad (2-2)$$

where s represents the pair (ϕ, z) and

$$\Delta(\rho) \equiv \frac{1}{\rho^2} \frac{\partial^2}{\partial \phi^2} + \frac{\partial^2}{\partial z^2} \quad (2-3)$$

Utilizing the fact that by hypothesis

$$\rho k \gg 1 \quad (2-4)$$

one has

$$\psi(\rho, s, t) = b(\rho, s) \frac{e^{ik\rho}}{\sqrt{\rho}} e^{-i\omega t} \quad (2-5)$$

Assuming that $\mu(\rho, s)$ is small, so that

$$(1 + \mu)^2 = 1 + 2\mu \quad (2-6)$$

and substituting Equation (2-5) into Equation (2-2) yields (Ref. 1)

$$2ik \frac{\partial b(\rho, s)}{\partial \rho} + \Delta(\rho) b(\rho, s) + 2k^2 \mu(\rho, s) b(\rho, s) = - \frac{\partial^2 b(\rho, s)}{\partial \rho^2} \quad (2-7)$$

where $b(\rho, s)$ satisfies the boundary condition

$$b(\epsilon, s) = 1 \quad (2-8)$$

The term $\partial^2 b / \partial \rho^2$ contributes backscattering to the solution of Equation (2-7). It will be disregarded here, and its effect will be estimated in the next section.

Following Reference 1, let the index of refraction covariance function be

$$E(\mu(\rho, s) \mu(\rho', s')) = \overline{\mu^2} \exp \left[- \frac{(\rho - \rho' \cos(\phi - \phi'))^2}{a^2} \right] \cdot \exp \left[- \frac{\rho'^2 \sin^2(\phi - \phi')}{a^2} \right] \exp \left[- \frac{(z - z')^2}{a^2} \right] \quad (2-9)$$

where a is correlation distance of the index of refraction.

Making the long range propagation approximation (Ref. 1) one has

$$E(\mu(\rho, s) \mu(\rho', s')) \simeq \sqrt{\pi} \overline{\mu^2} a \delta(\rho - \rho' \cos(\phi - \phi')) \cdot \exp \left[- \frac{\rho'^2 \sin^2(\phi - \phi')}{a^2} \right] \cdot \exp \left[- \frac{(z - z')^2}{a^2} \right] \quad (2-10)$$

Disregarding $\partial^2 b / \partial \rho^2$ in Equation (2-7) the resulting equation may be written as

$$2ik \exp(ik \Phi(\rho, s)) \frac{\partial}{\partial \rho} \left[\exp(-ik \Phi(\rho, s)) b(\rho, s) \right] = - \Delta(\rho) b(\rho, s) \quad (2-11)$$

where

$$\Phi(\rho, s) \equiv \int_{\epsilon}^{\rho} \mu(\rho', s) d\rho' \quad (2-12)$$

Multiplying both sides of Equation (2-11) by $\exp(-ik\Phi)$, integrating over ρ , and multiplying the resulting equation by $\exp(i\Phi)$ yields

$$\begin{aligned} 2ik b(\rho, s) = & 2ik \exp\left(ik \int_{\epsilon}^{\rho} \mu(\rho', s) d\rho'\right) \\ & - \int_{\epsilon}^{\rho} \exp\left(ik \int_{\rho'}^{\rho} \mu(\rho'', s) d\rho''\right) \Delta(\rho') b(\rho', s) d\rho' \end{aligned} \quad (2-13)$$

where the boundary condition

$$b(\epsilon, s) = 1 \quad (2-14)$$

was used in obtaining Equation (2-13).

Let it be assumed that $\int_{\epsilon}^{\rho} \mu(\rho', s) d\rho'$ is Gaussian either because $\mu(\rho, s)$ satisfies and appropriate central limit theorem or because $\mu(\rho, s)$ is a Gaussian field.

In Reference 1 it is shown that $b(\rho, s)$ is a functional of $\mu(\rho', s)$ with $\epsilon \leq \rho' \leq \rho$.

Then, due to the sharply peaked nature of the correlation function of $\mu(\rho, s)$,

$\int_{\rho'}^{\rho} \mu(\rho'', s) d\rho''$ is statistically independent of $b(\rho', s)$. Therefore, taking the expectation value of both sides of Equation (2-13) yields

$$\begin{aligned} 2ik E(b(\rho, s)) = & 2ik E\left(\exp\left(ik \int_{\epsilon}^{\rho} \mu(\rho', s) d\rho'\right)\right) \\ & - \int_{\epsilon}^{\rho} E\left(\exp\left(ik \int_{\rho'}^{\rho} \mu(\rho'', s) d\rho''\right)\right) \\ & \cdot \Delta(\rho') E(b(\rho', s)) d\rho' \end{aligned} \quad (2-15)$$

Using the fact that $\mu(\rho, s)$ is statistically homogeneous and isotropic it can be shown (Ref. 1) that $b(\rho, s)$ is statistically homogeneous and isotropic in s . Therefore $E(b(\rho, s))$ is a function of ρ only, so that

$$\Delta(\rho') E(b(\rho', s)) = 0 \quad (2-16)$$

and

$$\begin{aligned} E(b(\rho, s)) &= E \left(\exp \left(ik \int_{\epsilon}^{\rho} \mu(\rho', s) d\rho' \right) \right) \\ &\equiv \exp \left(- \frac{k^2}{2} E(\Phi^2(\rho, s)) \right) \end{aligned} \quad (2-17)$$

Using Equation (2-10) one obtains

$$\begin{aligned} E(\Phi^2(\rho, s)) &\simeq \sqrt{\pi} \overline{\mu^2} a \int_{\epsilon}^{\rho} \int_{\epsilon}^{\rho} \delta(\rho_1 - \rho_2) d\rho_1 d\rho_2 \\ &= \sqrt{\pi} \overline{\mu^2} a \rho \quad \rho \gg \epsilon, \rho \gg a \end{aligned} \quad (2-18)$$

Finally, one has

$$E(b(\rho, s)) = \exp \left(- \frac{\sqrt{\pi}}{2} \overline{\mu^2} k^2 a \rho \right) \quad (2-19)$$

This result is identical to the corresponding result for the plane wave case, obtained by Tatarskii (Ref. 2).

In the next section the region of validity of the forward scattering equation is obtained.

SECTION III

THE REGION OF VALIDITY OF THE FORWARD SCATTERING EQUATION

Let $B(\rho, s)$ be the solution of Equation (2-7), so that

$$2ik \frac{\partial B(\rho, s)}{\partial \rho} + \Delta(\rho) B(\rho, s) + 2k^2 \mu(\rho, s) B(\rho, s) = - \frac{\partial^2 B(\rho, s)}{\partial \rho^2} \quad (3-1)$$

Suppose Equation (3-1) were to be solved by successive approximation. Then, $B(\rho, s)$ is expanded in a perturbation series

$$B(\rho, s) = b(\rho, s) + b_1(\rho, s) + \dots \quad (3-2)$$

where

$$2ik \frac{\partial b(\rho, s)}{\partial \rho} + \Delta(\rho) b(\rho, s) + 2k^2 \mu(\rho, s) b(\rho, s) = 0 \quad (3-3a)$$

and

$$2ik \frac{\partial b_1(\rho, s)}{\partial \rho} + \Delta(\rho) b_1(\rho, s) + 2k^2 \mu(\rho, s) b_1(\rho, s) = - \frac{\partial^2 b(\rho, s)}{\partial \rho^2} \quad (3-3b)$$

Using the same type of manipulations which led to Equation (2-13), and the boundary condition

$$b_1(\epsilon, s) = 0 \quad (3-4)$$

Equation (3-3b) becomes

$$2ik b_1(\rho, s) = - \int_{\epsilon}^{\rho} \exp \left(ik \int_{\rho'}^{\rho} \mu(\rho'', s) d\rho'' \right) \cdot \left[\Delta(\rho') b_1(\rho', s) + \frac{\partial^2 b(\rho', s)}{\partial \rho'^2} \right] d\rho' \quad (3-5)$$

From the properties of $b(\rho, s)$ and $\mu(\rho, s)$ one finds that $b_1(\rho, s)$ is statistically isotropic and homogeneous in s , and that

$\int_{\rho'}^{\rho} \mu(\rho'', s) d\rho''$ is statistically independent of $b_1(\rho', s)$. Therefore taking the expectation value of both sides of Equation (3-5) yields

$$2ik E(b_1, (\rho, s)) = - \int_{\epsilon}^{\rho} E \left(\exp \left(ik \int_{\rho'}^{\rho} \mu(\rho'', s) d\rho'' \right) \right) \cdot \frac{\partial^2 E(b(\rho', s))}{\partial \rho'^2} \cdot d\rho' \quad (3-6)$$

Equations (2-9) and (2-19) one has

$$\begin{aligned} & E \left(\exp \left(ik \int_{\rho'}^{\rho} \mu(\rho'', s) d\rho'' \right) \right) \\ &= \exp \left(- \frac{k^2}{2} \cdot \sqrt{\pi} \overline{\mu^2} a \int_{\rho'}^{\rho} \int_{\rho'}^{\rho} \delta(\rho_1 - \rho_2) d\rho_1 d\rho_2 \right) \\ &= \exp \left(- \frac{\sqrt{\pi}}{2} \overline{\mu^2} k^2 a (\rho - \rho') \right) \end{aligned} \quad (3-7)$$

and

$$\frac{\partial^2 E(b(\rho', s))}{\partial \rho'^2} = \left(\frac{\sqrt{\pi}}{2} \overline{\mu^2} k^2 a \right)^2 \exp \left(- \frac{\sqrt{\pi}}{2} \overline{\mu^2} k^2 a \rho' \right) \quad (3-8)$$

Substituting Equations (3-7) and (3-8) into Equation (3-6) yields

$$\begin{aligned} E(b_1(\rho, s)) &= i \frac{\pi}{8} \left(\frac{3}{2} \left(\frac{1}{\mu^2} ka \right)^2 (k\rho) \exp \left(-\frac{\sqrt{\pi}}{2} \frac{1}{\mu^2} k^2 a \rho \right) \right) \\ &\equiv i \frac{\pi}{8} \left(\frac{3}{2} \left(\frac{1}{\mu^2} ka \right)^2 k\rho E(b(\rho, s)) \right) \quad \rho \gg \epsilon, \rho \gg a \quad (3-9) \end{aligned}$$

Then

$$\frac{|E(b_1(\rho, s))|}{E(b(\rho, s))} = \frac{\pi}{8} \left(\frac{3}{2} \left(\frac{1}{\mu^2} ka \right)^2 (k\rho) \right) \quad (3-10)$$

Thus, if

$$\frac{\pi}{8} \left(\frac{3}{2} \left(\frac{1}{\mu^2} ka \right)^2 (k\rho) \right) \ll 1 \quad (3-11)$$

the forward scattering equation is valid. These results are identical to the corresponding results for the plane wave case obtained by Tatarskii (Ref. 2).

SECTION IV

REFERENCES

1. M. M. Fitelson, "The Coherence for Cylindrically Spreading Waves in a Random Medium", to be published in JASA.
2. V. I. Tatarskii, "The Effects of the Turbulent Atmosphere on Wave Propagation", pp 377-381, 401-404. Israel Program for Scientific Translation, 1971. (Available in U. S. through NTIS).